



Face Material

High gloss wood free paper

Type Coated paper

Colour and Finish White

Weight 80 gsm \pm 3% ISO 536

Thickness 65 μ \pm 4% ISO 534

Adhesive

A special purpose extra permanent, rubber based adhesive.

Type Rubber permanent

Min. Appl.Temp 5 $^{\circ}$ c

Service TEMP +5/+80 $^{\circ}$ c

Initial Tack 10 N/25mm FINAT FTM 9

Shear Very High FINAT FTM18

Final Adhesion 8 N/25mm FINAT FTM 2

Liner

Type One side siliconized Glassine

Colour and Finish White

Weight 60 gsm \pm 5% ISO 536

Thickness 55 μ \pm 5% ISO 534

Transparency >50% DIN 53 147-46

Application

Specially designed for general and promotional labels in consumer product

Printing Methods

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 \pm 2 $^{\circ}$ c and 50 \pm 5 $^{\circ}$ c of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.