



Face Material

Gloss white top coated cavitated polypropylene
Type Top coated cavitated polypropylene
Colour and Finish Pearalized
Weight 46 gsm \pm 10% ISO 536
Thickness 66 μ \pm 10% ISO 534

Adhesive

General purpose Acrylic permanent featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP)
Type Acrylic based
Min. Appl.Temp 0 $^{\circ}$ c
Service TEMP -20/+80 $^{\circ}$ c
Initial Tack 8 N/25mm FINAT FTM 9
Shear High FINAT FTM18
Final Adhesion 7 N/25mm FINAT FTM 2

Liner

Type One side siliconised Glassine
Colour and Finish Yellow
Weight 60 gsm \pm 5% ISO 536
Thickness 55 μ \pm 5% ISO 534
Transparency >50% DIN 53 147-46

Application

Specially designed for logistic and promotional labels in consumer product

Printing Methods

Printable with letterpress, flexo , offset and gravure.
Testing for suitability between media , printers and inks is always recommended prior to use.

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 \pm 2 $^{\circ}$ c and 50 \pm 5 $^{\circ}$ c of relative Humidity.)
Keep the material in the original packaging when not used in order to protect it from dust and contamination
Do not expose to direct sunlight or heat sources.