



Face Material

Gloss silver metallized top coated polypropylene.

Type	Top coated polypropylene	
Colour and Finish	Gloss silver	
Weight	47 gsm ± 10%	ISO 536
Thickness	51 μ ± 10%	ISO 534

Adhesive

A general purpose permanent, rubber based adhesive

Type	Rubber permanent	
Min. Appl.Temp	0 °c	
Service TEMP	-30/+70 °c	
Initial Tack	10 N/25mm	FINAT FTM 9
Shear	Very High	FINAT FTM18
Final Adhesion	11 N/25mm	FINAT FTM 2

Liner

Type	One side siliconised Glassine	
Colour and Finish	Yellow	
Weight	60 gsm ±5%	ISO 536
Thickness	55 μ ± 5%	ISO 534
Transparency	>50%	DIN 53 147-46

Application

Specially designed for logistic and promotional labels in consumer product

Printing Methods

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23±2 °c and 50±5 % of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.