

Technical data sheet ROLL LABEL –BOPP film 12013201 PP Silver 51 TC - ACR GN - HG 59

Face Material

Gloss silver metalized top coated polypropylene

Туре	BOPP film	
Colour and Finish	Metallized	
Weight	47 gsm ± 3%	ISO 536
Thickness	51 μ ± 4%	ISO 534

Adhesive

General purpose Acrylic permanent featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP)

Туре	Acrylic based	
Min. Appl.Temp	0°c	
Service TEMP	-20/+80 °c	
Initial Tack	8 N/25mm	FINAT FTM 9
Shear	High	FINAT FTM18
Final Adhesion	7 N/25mm	FINAT FTM 2

Liner

Туре	One side siliconized glassine		
Colour and Finish	Honey		
Weight	59 gsm ±5%	ISO 536	
Thickness	55 μ ± 5%	ISO 534	
Transparency	>50%	DIN 53 147-46	

Issue date: Jun-2015

Application

Specially designed for logistics and promotional labels in consumer product

Printing Methods

Printable with letterpress, flexo, offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 ± 2 °c and 50 ± 5 °c of relative Humidity.) Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.