



### **Face Material**

Matt clear polypropylene

Type	polypropylene	
Colour and Finish	Matt clear	
Weight	54 gsm ± 3%	ISO 536
Thickness	58 μ ± 4%	ISO 534

### **Adhesive**

General purpose Acrylic permanent featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP)

Type	Acrylic based	
Min. Appl.Temp	0°c	
Service TEMP	-20/+80 °c	
Initial Tack	8 N/25mm	FINAT FTM 9
Shear	High	FINAT FTM18
Final Adhesion	7 N/25mm	FINAT FTM 2

### **Liner**

Type	One side siliconized Glassine	
Colour and Finish	Yellow	
Weight	62 gsm ±5%	ISO 536
Thickness	55 μ ± 5%	ISO 534
Transparency	>50%	DIN 53 147-46

### **Application**

Specially designed for promotional labels in consumer product

### **Printing Methods**

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

### **Shelf life**

Two years under storage conditions (This material must be stored at a temperature of 23±2 °c and 50±5 % of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.