



Technical data sheet
ROLL LABEL –BOPP film
11022015 PP white. gloss 51 TC - HTM. GN - WG 60

Issue date: Jun-2015

Face Material

Gloss white top coated polypropylene

Type	Top coated polypropylene	
Colour and Finish	white	
Weight	54 gsm ± 10%	ISO 536
Thickness	51 μ ± 10%	ISO 534

Adhesive

A general purpose permanent, rubber based adhesive

Type	Rubber permanent	
Min. Appl.Temp	0°c	
Service TEMP	-30/+70 °c	
Initial Tack	10 N/25mm	FINAT FTM 9
Shear	High	FINAT FTM18
Final Adhesion	11 N/25mm	FINAT FTM 2

Liner

Type	One side siliconized Glassine	
Colour and Finish	White	
Weight	60 gsm ±5%	ISO 536
Thickness	55 μ ± 5%	ISO 534
Transparency	>50%	DIN 53 147-46

Application

Specially designed for logistics and promotional labels in consumer product

Printing Methods

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23±2 °c and 50±5 % of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.